

BRUSHCUTTER

Bonhoeffer's Brush cutter BON-P-BC45 comes with 30% more powerful engine compared with traditional engines. Made with shear precision, it is compatible, lightweight, and has a 200 Hour tested Professional Gear Box. Our Brush cutter engine is fitted with 20 CRMO material Crankshaft for a longer service life. Ergonomic bicycle type handle helps to do outdoor work effectively. Brush cutter makes your daily task of cutting and trimming the uneven bushes, shrubs, and grass easy.



STANDARD EQUIPMENTS

			
Timmer Head	Blade	Harness	Deflector



FEATURES



STANDARD DOUBLE HARNESS

This brush cutter includes a standard harness, ideal for lighter brush cutters.



EFFICIENT FUEL PUMP

Featuring a fuel pump designed for effortless starting.



VERSATILE CUTTING GAURD

The combi-guard cutting attachment allows you to use either a grass blade or trimmer head, adding versatility to your work.



RUGGED HANDLE SYSTEM

Built for durability, the handlebar is securely attached to the tube using a die-cast clamp.




EFFICIENT AIR FILTRATION

Our efficient air filter not only reduces service costs but also minimizes engine wear.



OPTIMAL CUTTING PERFORMANCE

A bevel gear with high torque ensures that the cutting equipment remains parallel to the ground, delivering exceptional cutting performance.



HEAVY-DUTY CLUTCH

A heavy-duty clutch enables you to tackle demanding tasks with ease, even when using long cords and a large-diameter cutting knife.



USER-FRIENDLY STARTER

The stand-alone starter simplifies starter cord replacement when needed.

TECHNICAL SPECIFICATIONS

Technical data Engine Cylinder displacement Power output Maximum power speed Clutch engaged speed Fuel tank volume	44.8 cm ³ / 2.73 cu.inch 1.6 kw 10000 rpm 4200 rpm 920 ml
Technical data Idle speed Spark plug Electrode gap	2700 - 3000 rpm NGK BPMR7A 0.5 - 0.7 mm
Vibration & noise data Sound pressure level at operators ear	95 dB(A)
Transmission data Gear ratio Drive gear angle	19:14 30 °
Equipment OEM Trimmer head OEM Saw blade OEM Harness	Techomac- M10 2 T Blade-305mm Standard double harness
Overall dimensions Weight (excl. cutting equipment) Tube diameter	8.7 kg / 19.2 lbs 28 mm